



TOLBER DIVISION
PYRAMID PLASTICS, INC.



Technical Information Data

MICCROTAPE SELF-WOUND VINYL TAPE

DESCRIPTION:

Chemical resistant adhesive won't contaminate plating baths. Holds a straight edge when masking parts for anodizing or electroless nickel plating. It has firm elongation properties.

CONSTRUCTION

Adhesive:	Rubber
Backing:	6 mil vinyl
Standard Roll Length:	66 feet
Temperature Resistance:	15 ° F to 220 ° F
Color:	Black

FEATURES:

Conformable vinyl backing.
Completely masks off area.
Chemical, temperature resistant.
Withstands treatment baths.
Economical roll size.
Saves time and money.

APPLICATION:

1. Nickel plating and anodizing mask off.
2. To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain a good adherence to surface contact.

Alternative to 3M 470-471

3. Note: Values should not be used for specification purposes. Each user should make their own test to determine the product's suitability for their own intended use and shall assume all risks and liability in connection herewith. Materials should be stored at 70 ° F (21 ° C) with 50% relative humidity.



80 Metcalfe Street
Buffalo, NY 14206
716.856.2300
716.856.7115 (fax)
sales@cdibuffalo.com

