



B SERIES, 1 1/4" SMALL TANK METAL HEATERS							
WATTS	VOLTS	HOT ZONE In./(mm)	OVERALL LENGTH In./(mm)	304 SS	316 SS	TITANIUM	SHIP WGT. Lbs./(kg)
500	120	5	10	FB.5110-**	SB.5110-**	TB.5110-**	5
	240	(130)	(255)	FB.5210-**	SB.5210-**	TB.5210-**	(2)
1000	120	8	14	FB1114-**	SB1114-**	TB1114-**	6
	240	(205)	(355)	FB1214-**	SB1214-**	TB1214-**	(3)
1500	120	11	17	FB1.5117-**	SB1.5117-**	TB1.5117-**	8
	240	(280)	(430)	FB1.5217-**	SB1.5217-**	TB1.5217-**	(3.5)

Product Features and Benefits:

- ◆ **SUPERIOR CHEMICAL RESISTANCE:** Materials available for use in most aqueous alkaline solutions, plating solutions, and rinse tanks. Check solution recommendation chart or with your chemical supplier for proper sheath material selection.
- ◆ **RUGGED CONSTRUCTION:** Heavy wall metal sheaths available in:
 - 304 stainless steel.
 - 316 stainless steel.
 - Titanium.
- ◆ **OUTSTANDING PERFORMANCE:** Watt densities of 45 watts per square inch (6.9 w/cm²) ensure long service life.
- ◆ **CORROSION RESISTANT HEAD:** Vapor tight, flame resistant polypropylene terminal enclosure with 3-foot (.9m) flexible PVC liquid tight conduit.
- ◆ **SAFETY FEATURES:**
 - Grounded construction.
 - Thermal protector built in. Replaceable P1 fuse standard for solutions up to 180°F (82°C).
 - Non-floating construction.
- ◆ **CERTIFICATIONS:** UL listed to U.S. and Canadian safety requirements, and CE.
- ◆ **SIZES:** 500 watts to 2,000 watts.
- ◆ **VOLTAGES:** 120 to 415 volts. Single phase only.
- ◆ **OPTIONS AVAILABLE (consult factory):**
 - Replaceable thermal protectors:
 - P4: for solutions from 180°F (82°C) to 230°F (110°C).
 - Resettable thermal protectors:
 - P2: for solutions up to 180°F (82°C).
 - P6: for solutions from 180°F (82°C) to 230°F (110°C).
 - Special configurations and lengths.
 - Longer wire and conduit lengths.
 - Pre-wired plug-in connector for easy and quick installation.
 - Lower watt densities for highly viscous solutions.
 - Temperature and level controls sized to match the heater.

Your Distributor:

80 Metcalfe Street • Buffalo, NY 14206 U.S.A. • **US/CN: 800-777-2436** • 716-856-2300 • Fax: 716-856-7115

www.cdibuffalo.com • E-mail: sales@cdibuffalo.com

